e-KON WATER BOOSTER

The Sencillo Booster System is our lowest cost duplex packaged pre-piped and wired pumping system, designed to provide a constant water pressure with varying demand for flow.

SS0003 1126
Supercedes 0925

Automatic Operation

- Speed varies to maintain constant pressure
- Alternation between pumps
- Shuts off during no-flow periods.
- Shuts down on loss of source water with auto-start.
- Shuts down on high outlet pressure with auto-restart.
- Auto switch to backup pump on pump failure
- Complete alarm package

Easy 5 Step Installation

- Bolt to floor
- Run power wire to panel
- Attach inlet/outlet pipes
- Open valves
- TURN IT ON

Unit is ready to pressurize the building

Technical Data

Pumps	NSF61 listed end suction centrifugal with motor
Number of Pumps	2
HP	Up to 7.5 HP
Controller	NEMA 1 Ventilated
Pipe Connections	304SS-NPT, flanged or grooved
Valves	Inlet/outlet isolation valves. Outlet check valves
Frame	Powder-coated steel
Hydro Tank	All sizes available
Pressure Gauges	Liquid filled
Max. Outlet Pressure	None. Project specific
Skid Size (Typical)	35”W x 42L x 72”H
Voltage	1/208, 1/240V 3/208-230V 3/480V
Approval	Conforms to NSF 61/372 standard for safe lead free drinking water*

*UL/cUL listed pumping system







STANDARD FEATURES

(UL508A Listed)

- Power package with
  - Main disconnect switch with thru-the-door handle
  - Customer wire terminal block
  - Motor circuit breaker for each pump
  - Variable speed drive for each pump
- Low voltage (24VDC) controls package with
  - Circuit breaker
  - Power supply
  - PLC
  - Color touch screen with graphics package
  - All control settings selected on touch screen

Other questions? Lets talk.
Call 610-340-2848 or visit www.SencilloSystems.com

SENCILLO™
SIMPLE.

Sencillo Systems • 2381 Philmont Avenue #125 Huntingdon Valley PA 19006 • Tel: 610.340.2848
www.SencilloSystems.com • © Sencillo Systems. All rights reserved.